

## PREFABRICATED ROUND CABLES WITH ELCO/EDAC CONNECTOR

### Features

- Shielded/ non shielded cable assembly is available.
- Available in all customize lengths.
- Shielded/Non Shielded cable assembled with ELCO/EDAC connectors at both ends/one end and other end open fitted with ferrules / lugs.
- Available in -20/38/56/90/120

### Specifications

- Cable conductor cross-section - AWG26/0.14 mm<sup>2</sup>
- Max. permissible current capacity per path-2A.
- Operating Voltage- 125V AC/DC.



### TECHNICAL INFORMATION

Prefabricated non- shielded round cables with ELCO/EDAC connector			Prefabricated shielded round cables with ELCO/EDAC connector		
Article Nos.	Descriptions	No. of Pos.	Article Nos.	Descriptions	No. of Pos.
11100509:n	AE- CABLE-ELCO 20/n	20	11100565:n	AE- CABLE-Sh/ELCO 20/n	20
11100510:n	AE- CABLE-ELCO 38/n	38	11100566:n	AE- CABLE-Sh/ELCO 38/n	38
11100511:n	AE- CABLE-ELCO 56/n	56	11100567:n	AE- CABLE-Sh/ELCO 56/n	56
11100512:n	AE- CABLE-ELCO 90/n	90	11100568:n	AE- CABLE-Sh/ELCO 90/n	90
11100513:n	AE- CABLE-ELCO 120/n	120	11100569:n	AE- CABLE-Sh/ELCO 120/n	120
11100514:P:n	AE- CABLE-ELCO 20/DNP/n	20	11100570:P:n	AE- CABLE-Sh/ELCO 20/DNP/n	20
11100515:P:n	AE- CABLE-ELCO 38/DNP/n	38	11100571:P:n	AE- CABLE-Sh/ELCO 38/DNP/n	38
11100516:P:n	AE- CABLE-ELCO 56/DNP/n	56	11100572:P:n	AE- CABLE-Sh/ELCO 56/DNP/n	56
11100517:P:n	AE- CABLE-ELCO 90/DNP/n	90	11100573:P:n	AE- CABLE-Sh/ELCO 90/DNP/n	90
11100518:P:n	AE- CABLE-ELCO 120/DNP/n	120	11100574:P:n	AE- CABLE-Sh/ELCO 120/DNP/n	120

**Note** DNP : Design Number 1,2... M : Male connector  
 BE : Both end F : Female connector  
 n : length in meter